



<b>Technische Daten / Technical specifications:</b>		<b>Hochelastische Kupplung Größe 15 / Highly elastic coupling size 15</b>	<b>Bohrungskombination / drilling combination</b>			
---	--	---	---	--	--	--

			d1/d2	6	8	10	12
Max. Drehzahl / Max. RPM	min <sup>-1</sup>	3000	6	x	x	x	x
Max. Drehmoment / Max. torque	Nm	1,5	8		x	x	x
Max. Wellenversatz radial / Max. Radial shaft offset	mm	± 2,5	10			x	x
Max. Wellenversatz axial / Max. Axial shaft misalignment	mm	± 3	12				x
Max. Winkel Wellenversatz / Max. Angle shaft offset	Grad	± 10					
Drehfedersteife / torsion spring stiffness	Nm/rad	25					
Radialfedersteife / radial spring stiffness	N/mm	15					
Trägheitsmoment / moment of inertia	gcm <sup>2</sup>	104					
Max. Drehmoment d. Schrauben / max. clamping torque	Ncm	200					
Temperaturbereich / temperature range	°C	-30° bis +80°					
Gewicht / weight appr.	g	48					
Werkstoff Flansch / material flange		VA / stainless steel					
Verbindungselement / connecting element		Polyurethan / polyurethane					

**Bestellbeispiel / Example**  
**Hochelastische Kupplung Gr15 d=8/12**

